

# CONSOLIDATED CHEMICAL CO. ABN: 34 527 060 773 ACN: 005 056 502

52-62 Waterview Close, DANDENONG SOUTH, 3175 P.O. BOX 4415, DANDENONG SOUTH, 3164, VIC, AUSTRALIA. PHONE: (03) 9799 7555 FAX: (03) 9799 7666 24 Hour Emergency Response: 1800 839 984 E-mail: sales@conchem.com.au Website: www.conchem.com.au

### **MAGNESIUM SULPHATE BP**

### **CONSOLIDATED CHEMICAL CO**

Chemwatch: 10490 Version No: 5.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 1

Issue Date: 27/06/2017 Print Date: 15/09/2017 S GHS AUS EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	MAGNESIUM SULPHATE BP
Chemical Name	magnesium sulfate, heptahydrate
Chemical formula	O4SMg.7H2O H2O4S.Mg
Other means of identification	3347, 676, 138, 626
CAS number	10034-99-8

### Relevant identified uses of the substance or mixture and uses advised against

Relevant	identified
	uses

Used in weighting cotton and silk; increasing the bleaching action of chlorinated lime; manufacture of mother-of-pearl and frosted papers; fire-proofing fabrics; dyeing and printing calicos; in fertilisers. Used in explosives, matches, mineral water, tanning leather and dietary supplements.

### Details of the supplier of the safety data sheet

Registered company name	CONSOLIDATED CHEMICAL CO
Address	52-62 Waterview Close 3175 Australia
Telephone	03 9799 7555
Fax	03/9799 7666
Website	Not Available
Email	Not Available

### **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	1800 839 984
Other emergency telephone numbers	Not Available

### **CHEMWATCH EMERGENCY RESPONSE**

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	1800 039 008	+612 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

#### **SECTION 2 HAZARDS IDENTIFICATION**

Page 2 of 9

**MAGNESIUM SULPHATE BP** 

Issue Date: **27/06/2017**Print Date: **15/09/2017** 

#### Classification of the substance or mixture

### NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification	Not Applicable
Label elements	

Hazard pictogram(s)	Not Applicable
SIGNAL WORD	NOT APPLICABLE

### Hazard statement(s)

Not Applicable

### Supplementary statement(s)

Not Applicable

### Precautionary statement(s) Prevention

Not Applicable

### Precautionary statement(s) Response

Not Applicable

### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

Not Applicable

### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

### **Substances**

CAS No	%[weight]	Name
10034-99-8	>95	magnesium sulfate, heptahydrate

### **Mixtures**

See section above for composition of Substances

### **SECTION 4 FIRST AID MEASURES**

### **Description of first aid measures**

Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Magnesium is present in the blood, as a normal constituent, at concentrations between 1.6 to 2.2 meq/L. Some 30% is plasma bound. At serum

Chemwatch: 10490 Page 3 of 9 Version No: 5.1.1.1

#### **MAGNESIUM SULPHATE BP**

Issue Date: 27/06/2017 Print Date: 15/09/2017

magnesium levels of 3-4 meq/L, signs of CNS depression, loss of reflexes, muscular tone and power, and bradycardia occur. Cardiac arrest (sometimes fatal) and/or respiratory paralysis can occur at plasma levels of 10-15 meq/L. For acute or short term repeated exposures to magnesium:

- ▶ Symptomatic hypermagnesaemia appears rarely in the absence of intestinal or renal disease.
- Elevated magnesium levels may cause hypocalcaemia because of decreased parathyroid hormone activity and decreased end-organ responsiveness.
- Patients with severe hypermagnesemia may develop sudden respiratory arrest and must be watched closely for apnoea.
- Use fluids, then vasopressors for hypotension. Frequently hypotension responds to calcium administration.
- Induce emesis or administer lavage if patient presents within 4 hours of ingestion. Use sodium cathartics, with caution, in presence of cardiac or renal failure.
- Activated charcoal is not useful.
- ▶ Calcium is an antagonist of magnesium action and is an effective antidote when serum levels exceed 5 meq/L and the patient exhibits symptoms. The adult dose of calcium gluconate is 10 ml of a 10% solution over several minutes. [Ellenhorn and Barceloux: Medical Toxicology]

#### **SECTION 5 FIREFIGHTING MEASURES**

Fire Incompatibility None known.

### **Extinguishing media**

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

### Special hazards arising from the substrate or mixture

Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>Decomposition may produce toxic fumes of:         <ul> <li>sulfur oxides (SOx)</li> <li>metal oxides</li> </ul> </li> <li>May emit poisonous fumes.</li> </ul>

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

**HAZCHEM** 

See section 12

### Methods and material for containment and cleaning up

Not Applicable

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	Moderate hazard.  • CAUTION: Advise personnel in area.  • Alert Emergency Services and tell them location and nature of hazard.  • Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling

▶ Avoid all personal contact, including inhalation.

▶ Wear protective clothing when risk of exposure occurs. Safe handling

▶ Use in a well-ventilated area.

Chemwatch: 10490 Page 4 of 9 Issue Date: 27/06/2017 Version No: 5.1.1.1 Print Date: 15/09/2017

#### MAGNESIUM SULPHATE BP

	▶ Prevent concentration in hollows and sumps.
Other information	<ul> <li>Plastic bag</li> <li>NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.</li> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry area protected from environmental extremes.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

### Conditions for safe storage, including any incompatibilities

#### ▶ Glass container is suitable for laboratory quantities Suitable container ▶ Polyethylene or polypropylene container. • Check all containers are clearly labelled and free from leaks. Derivative of very electropositive metal. Inorganic alkaline earth metal derivative. • Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride. Storage ► These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with incompatibility recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results.



- Must not be stored together
- May be stored together with specific preventions
- May be stored together

### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Control parameters**

### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Not Available

### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
magnesium sulfate, heptahydrate	Magnesium sulfate heptahydrate	10 mg/m3	110 mg/m3	660 mg/m3
magnesium sulfate, heptahydrate	Magnesium sulfate (1:1)	20 mg/m3	220 mg/m3	1,300 mg/m3

Ingredient	Original IDLH	Revised IDLH
magnesium sulfate, heptahydrate	Not Available	Not Available

### **Exposure controls**

### Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. **Appropriate** The basic types of engineering controls are: engineering controls Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Personal protection ▶ Safety glasses with side shields. Eye and face Chemical goggles. protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy

### Issue Date: 27/06/2017 Print Date: 15/09/2017

#### MAGNESIUM SULPHATE BP

	▶ document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.  Personal hygiene is a key element of effective hand care.  Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.  • polychloroprene.  • nitrile rubber.  • butyl rubber.
Body protection	See Other protection below
Other protection	► Overalls.  ► P.V.C. apron.  ► Barrier cream.
Thermal hazards	Not Available

### Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

### Information on basic physical and chemical properties

Appearance	Slightly soluble in alcohol, glycerol. Solubility in water @ 20 deg.C: 70 g/100 cc. @ 40 deg.C: 91 g/100 cc. Melting point: -6H2O @ 150 deg.C Boiling point: -7H2O @ 200 deg.C		
Physical state	Divided Solid	Relative density (Water = 1)	1.68
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not available.
pH (as supplied)	Not Applicable	Decomposition temperature	Not available.

Colourless, rhombic or monoclinic crystals; freely soluble in water. Odourless or almost odourless and saline, bitter taste.

Chemwatch: 10490 Version No: **5.1.1.1**  Page 6 of 9

Issue Date: 27/06/2017 Print Date: 15/09/2017 **MAGNESIUM SULPHATE BP** 

Melting point / freezing point (°C)	Not available.	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not available.	Molecular weight (g/mol)	246.47
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### **SECTION 11 TOXICOLOGICAL INFORMATION**

### Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  Levels above 10 micrograms per cubic metre of suspended inorganic sulfates in the air may cause an excess risk of asthmatic attacks in susceptible people.  Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.  If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.   Levels above 10 ug/m3 of suspended sulfates in the air may cause an excess risk of asthmatic attacks in susceptible persons.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.  Sulfates are not well absorbed orally, but can cause diarrhoea.  Magnesium salts are generally absorbed so slowly that swallowing these cause few toxic effects, with purging being the most significant. If it cannot be removed (for example in bowel obstruction or paralysis), it may irritate the gut lining and be absorbed into the body.  Side effects of magnesium salts include upset stomach, dry mouth, dry nose, dry throat, drowsiness, nausea, heartburn, and thickening of the lining of the throat and nose.  The magnesium ion causes salt disturbances, central nervous system depression, involvement of the heart, loss of reflexes and death from paralysis of breathing; these effects, however, are rare without pre-existing kidney or bowel disorders.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Chemwatch: 10490 Page 7 of 9 Issue Date: 27/06/2017 Version No: 5.1.1.1 Print Date: 15/09/2017

### **MAGNESIUM SULPHATE BP**

	May cause stinging sensation when in contact with skin cuts.			
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.			
Chronic	There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.  In a case of chronic abuse of magnesium citrate, symptoms seen included tiredness and severe low blood pressure which did not respond to treatment. Blood tests revealed extremely high levels of magnesium, and the patient was found to have a perforated ulcer of the duodenum. Kidney failure and death followed.  A patient with normal kidney function developed stoppage of breathing and slow heart rate after receiving 90 grams of magnesium sulfate over 18 hours.  Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.  Levels above 10 micrograms per cubic metre of suspended inorganic sulfates in the air may cause an excess risk of asthmatic attacks in susceptible people.   A patient with normal kidney function developed symptomatic hypermagnesaemia with respiratory arrest and bradycardia after receiving 90 grams of magnesium sulfate over 18 hours. When given to pregnant rats, a sharp reduction of both the number and the weight of the offspring was observed.			
	TOVICITY	IDDITATION		
magnesium sulfate,	TOXICITY	IRRITATION		
heptahydrate	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available		
	Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>			

MAGNESIUM SULFATE, HEPTAHYDRATE	Oral (man) TDLo: 183 mg/kg/4h-l Nil reported			
Acute Toxicity	X	Carcinogenicity	0	
Skin Irritation/Corrosion	0	Reproductivity	0	
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0	
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0	
Mutagenicity	0	Aspiration Hazard	0	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS.

Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

X - Data available but does not fill the criteria for classification

✓ – Data available to make classification

### **SECTION 12 ECOLOGICAL INFORMATION**

Legend:

### **Toxicity**

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	2820mg/L	4
magnesium sulfate,	EC50	48	Crustacea	343.56mg/L	4
heptahydrate	EC50	72	Algae or other aquatic plants	=2700mg/L	1
	EC0	72	Algae or other aquatic plants	=220mg/L	1
	NOEC	504	Crustacea	360mg/L	4
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

for magnesium compounds in general:

Fish LC50: 100-400 mg/l

#### For Inorganic Sulfate:

Environmental Fate - Sulfates can produce a laxative effect at concentrations of 1000 - 1200 mg/liter, but no increase in diarrhea, dehydration or weight loss. The presence of sulfate in drinking-water can also result in a noticeable taste. Sulfate may also contribute to the corrosion of distribution systems. No health-based guideline value for sulfate in drinking water is proposed.

### MAGNESIUM SULPHATE BP

Issue Date: **27/06/2017**Print Date: **15/09/2017** 

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Environmental Fate: Environmental processes, such as oxidation, the presence of acids or bases and microbiological processes, may transform insoluble metals to more soluble ionic forms. Environmental processes may enhance bioavailability and may also be important in changing solubilities.

Aquatic/Terrestrial Fate: When released to dry soil, most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into ground water and/ or surface water ecosystems when soaked by rain or melt ice. A metal ion is considered infinitely persistent because it cannot degrade

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
magnesium sulfate, heptahydrate	HIGH	HIGH

#### Bioaccumulative potential

Ingredient	Bioaccumulation
magnesium sulfate, heptahydrate	LOW (LogKOW = -2.2002)

### Mobility in soil

Ingredient	Mobility
magnesium sulfate, heptahydrate	LOW (KOC = 6.124)

#### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ▶ Reuse
- ▶ Recycling
- ► Disposal (if all else fails)

## Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ► DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

#### **SECTION 14 TRANSPORT INFORMATION**

### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### **SECTION 15 REGULATORY INFORMATION**

Chemwatch: **10490** Page **9** of **9** Issue Date: **27/06/2017** 

Version No: 5.1.1.1 MAGNESIUM SULPHATE BP Print Date: 15/09/2017

### MAGNESIUM SULFATE, HEPTAHYDRATE(10034-99-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (magnesium sulfate, heptahydrate)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (magnesium sulfate, heptahydrate)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### **SECTION 16 OTHER INFORMATION**

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

 $\begin{tabular}{ll} PC-TWA: Permissible Concentration-Time Weighted Average \\ PC-STEL: Permissible Concentration-Short Term Exposure Limit \\ \end{tabular}$ 

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.